



PCT/EP 03/08296

REC'D 01 SEP 2003	
WIPO	PCT



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


BEST AVAILABLE COPY

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c.; plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed

Stephen Hordley

Dated 27 May 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)THE PATENT OFFICE
AThe
Patent
Office

- 5 AUG 2002

RECEIVED BY FAX

Request for grant of a patent

(See the notes on the back of this form. You can also
get an explanatory leaflet from the Patent Office to
help you fill in this form.)05AUG02 E738265-1 000066
The Patent Office
P01/7700 0.00-0218010.7
Cardiff Road
Newport
Gwent NP9 1RH

1.	Your reference	GB Case	GT/3-22331/P1
2.	Patent application number (The Patent Office will fill in this)	0218010.7 - 5 AUG 2002	
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	Ciba Specialty Chemicals Water Treatments Limited Cleckheaton Road Low Moor Bradford West Yorkshire BD12 0JZ 7585391004 England	
	Patent ADP number (if you know it)	7585391004	
	If the applicant is a corporate body, give the country/state of its incorporation	England	
4.	Title of invention	PRODUCTION OF A FERMENTATION PRODUCT	
5.	Name of your agent (if you have one)	Ciba Specialty Chemicals Water Treatments Limited	
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Patents Department PO Box 38 Cleckheaton Road Low Moor Bradford West Yorkshire BD12 0JZ 7585391002	
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)
			Date of filing (day/month/year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:	YES	
	a) any applicant named in part 3 is not an inventor, or		
	b) there is an inventor who is not named as an applicant, or		
	c) any named applicant is a corporate body.		
	(see note (d))		

Patents Form 1/77

0043467 05-AUG-02 09:38

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 14

Claim(s) 2

Abstract 1

Drawing(s)

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application

Signature

Date

C. Choppen

5 August 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Catherine Choppen 01274 417446

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 23 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) Once you have filled in the form you must remember to sign and date it.
- e) For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

GT/3-22331/P1

DUPLICATE

1

Production of a Fermentation Product

The present invention relates to processes of treating plant derived material to provide an aqueous liquor containing sugars, which are used in a fermentation process to produce a fermentation product. Typically such fermentation products include for instance ethanol, glycerol, acetone, n-butanol, butanediol, isopropanol, butyric acid, methane, citric acid, fumaric acid, lactic acid, propionic acid, succinic acid, itaconic acid, acetic acid, acetaldehyde, 3-hydroxy propionic acid, glyconic acid and tartaric acid and amino acids such as L-glutaric acid, L-lysine, L-aspartic acid, L-tryptophan, L-arylglycines or salts of any of these acids.

It is known to treat shredded cellulosic material using concentrated acid to provide aqueous solutions of sugars, which can be used in a fermentation process. For instance US-A-4650689 discloses a process of preparing ethanol from cellulosic material by subjecting the cellulosic material to highly concentrated mineral acid gas such as HCl under pressure, and treatment with hot water to give a liquor containing sugars which can be fermented.


US-A-5975439 describes an automated process for producing ethanol by shredding the cellulosic component of municipal solid waste and mixing this with equal amounts of concentrated sulphuric acid at high temperature to provide a digested mixture. The aqueous sugar solution is separated from the solids by a filtration process before being subjected to a fermentation process.

However, it would be desirable to be able to increase the production of the fermentation products such as ethanol. In particular, it would be desirable to improve the drainage properties of acid treated plant derived material in order to maximise sugar recovery. Further, the solid product that results from the separation step should be as dry as possible in order to prevent any loss of sugar, which would otherwise be used in the fermentation process. In addition, the solid by product, which contains mainly lignin can be used as a solid fuel, for instance for use in the boiler used to heat the distillation column used in separating the

fermentation product from the fermentation broth. Thus, it is also desirable that should the solid lignin-containing product be used as a fuel, it should be as dry as possible. In addition, during separation of the solid matter from the aqueous phase, it is preferred to wash the solid matter with water, thus producing wash water. However, this wash water may contain impurities, e.g. If process liquors are recycled, which could be harmful to the fermentation process. Therefore, it would be desirable to minimise the amount of wash water used.

Accordingly, a process has been found, which improves the separation of solid matter from the liquid phase of an aqueous mixture comprising dissolved sugar, wherein a flocculating agent is added to the aqueous mixture in an effective amount, and which avoids the abovementioned disadvantages.

Preferably, this inventive process is part of a larger process, which yields a fermentation product such as the abovementioned alcohols, acids etc. Hence,



obtained by hydrolysing polysaccharide based plant derived material. Such a process is described in further detail below. As the hydrolysis preferably is carried out under acidic conditions, the aqueous mixture usually contains the acid applied for the hydrolysis of the polysaccharide based plant derived material.

Sugar means a carbohydrate, which is a ketonic (ketose) or aldehydic (aldose) derivative of a higher poly-alcohol. Preferably, sugar means a monosaccharide (having the general structure $C_nH_{2n}O_n$ with n from 2 to 6) or an oligosaccharide such as cellobiose, sucrose, particularly preferred are glycolaldehyde, glyceraldehyde, dihydroxyacetone, erythrose, threose, as well as aldopentoses, aldohexoses and ketohexoses such as glucose, fructose, maltose, arabinose, ribose, xylose, mannose, galactose, allose, gulose, altrose, idose, talose, ribulose, erythrulose, xylulose, psicose, sorbose and tagatose, lyxose, ribofuranose, arabinofuranose, ribopyranose, arabinopyranose, allofuranose, altrofuranose, glucofuranose, mannofuranose, allopyranose, altropyranose, glucopyranose, mannopyranose, xylofuranose, lyxofuranose, xylopyranose,

gulofuranose, idofuranose, glactofuranose, talofuranose, gulopyranose, idopyranose, galactopyranose, talopyranose, erythro-pentulose, threo-pentulase, psicofuranose, fructofuranose, sorbofuranose, tagatofuranose, psicopyranose, fructopyranose, sorbopyranose and tagatopyranose.

Solid matter means particles, which are not dissolved under the given hydrolysis conditions and generally comprise cellulose, lignin and analogous materials.

Suitably the flocculating agent is selected from the group consisting of water-soluble, water-swellaable natural, semi-natural and synthetic polymers and charged microparticulate material.

In a preferred embodiment of this invention, the flocculating agent would be added as an aqueous solution or aqueous dispersion. The flocculating agent is added in an amount sufficient to effect flocculation.

Typically the amount of polymeric flocculating agent sufficient to induce flocculation would be usually from 0.002 to 1, preferably from 0.01 to 1, more preferably from 0.02 to 0.2% by weight, based on the weight of the solid matter.

Therefore, preferably the amount of flocculating agent is chosen in the range of from 0.002 to 1% by weight, based on the weight of solid matter.

Following flocculation of the suspended solids the solid product can be separated from the hydrolysate aqueous liquor by mechanical means, for instance filter press, centrifuge, belt press, horizontal belt filter or pressure filter.

Preferably the polymer is synthetic and may be formed by polymerisation of at least one cationic, non-ionic or and/or anionic monomer(s) alone or with other water-soluble monomers. By water-soluble we mean that the monomer has a solubility of at least 5 g/100 ml at 25°C.

Preferably polymeric flocculating agents are formed from ethylenically unsaturated water-soluble monomers that readily polymerise to produce high molecular weight polymers. Particularly preferred polymers are e.g. polyacrylate salts, polyacrylamide, copolymers derived from acrylamide and (meth)acrylic acid or salts thereof, copolymers derived from acrylamide and dialkylaminoalkyl (meth)acrylate acid salt or quaternary ammonium salts, polymers derived from diallyldimethyl ammonium chloride, polyamines and polyethylene imines. The polymers may be linear, branched or cross-linked.

The polymers may be prepared by any convenient conventional process, for instance by solution polymerisation, gel polymerisation, reverse phase suspension polymerisation and reverse phase emulsion polymerisation. Suitable processes include those described in EP-A-150933 or EP-A-102759.

Suitable polymers can be anionic, cationic or non-ionic, preferably cationic. The intrinsic viscosity preferably is not less than 4 dl/g. Such an intrinsic viscosity generally indicates a polymer having a molecular weight of several million g/mol, for instance generally greater than 5,000,000 g/mol and usually at least 7,000,000 g/mol.

In general the cationic polymer preferably has an intrinsic viscosity greater than 6 dl/g, often at least 8, particularly more than 9 dl/g. The intrinsic viscosity can be as high as 30 dl/g or higher. In many cases though suitable cationic polymers exhibit an intrinsic viscosity in the range of 7 to 25 dl/g, in particular 10 to 20 dl/g, in particular around 14 to 15 dl/g.

Suitable cationic monomers include quaternary ammonium or acid salts of monomers, which contain amine groups. Preferably the cationic polymer is formed from a monomer or blend of monomers comprising at least one cationic monomer selected from the group consisting of quaternary ammonium and acid salts of dimethylaminoethyl (meth) acrylate, quaternary ammonium and acid salts of dimethylaminoethyl (meth) acrylamide and diallyldimethyl ammonium chloride.

The cationic monomers may be homopolymerised or copolymerised with other monomers, for instance acrylamide. The cationic polymers thus may be any polymer that carries a cationic charge, provided of course that they are of sufficiently high molecular weight to exhibit an intrinsic viscosity of at least 4 dl/g.

In general, intrinsic viscosity is measured using a suspended level viscometer in 1M NaCl buffered to pH 7.5 at 25°C.

The cationic polymers according to the invention may be prepared as substantially linear polymers or as branched or structured polymers. Structured or branched polymers are usually prepared by inclusion of polyethylenically unsaturated monomers, such as methylene-bis-acrylamide into the monomer mix, for instance as given in EP-B-202780. Preferably however, the polymers are substantially linear. In addition, it is preferred to choose the polymers in the form of a bead or powdered product.

In a further preferred embodiment of the present invention the flocculating agent is a charged microparticulate material. Particularly suitable examples of charged microparticulate materials include swellable clays, anionic, cationic or amphoteric microparticulate silica based materials and organic cross-linked polymeric microparticles.

The siliceous material may be any of the materials selected from the group consisting of silica based particles, silica microgels, colloidal silica, silica sols, silica gels, polysilicates, aluminosilicates, polyaluminosilicates, borosilicates, polyborosilicates, zeolites or swellable clay.

This siliceous material may be in the form of an anionic microparticulate material. Alternatively the siliceous material may be a cationic silica. Desirably the siliceous material may be selected from silicas and polysilicates.

The polysilicates of the invention may be prepared by acidifying an aqueous solution of an alkali metal silicate. For instance polysilicic microgels otherwise

known as active silica may be prepared by acidification of alkali metal silicate to between pH 2 and 10 by use of mineral acids or acid exchange resins, acid salts and acid gases. It may be desired to age the freshly formed polysilicic acid in order to allow sufficient three-dimensional network structure to form. Generally the time of ageing is insufficient for the polysilicic acid to gel. Particularly preferred siliceous materials include polyalumino-silicates. The polyaluminosilicates may be for instance aluminated polysilicic acid, made by first forming polysilicic acid microparticles and then post treating with aluminium salts.

Alternatively the polyaluminosilicates may be polyparticulate polysilicic microgels of surface area in excess of $1000\text{m}^2/\text{g}$ formed by reacting an alkali metal silicate with acid and water-soluble aluminium salts. Typically the polyaluminosilicates may have a mole ratio of alumina:silica in the range of 1:10 to 1:1500.

Polyaluminosilicates may be formed by acidifying an aqueous solution of alkali metal silicate to between pH 2 and 10 using concentrated sulphuric acid containing 0.2 to 2.0% by weight of a water soluble aluminium salt, for instance aluminium sulphate. The aqueous solution may be aged sufficiently for the three dimensional microgel to form. Typically the polyaluminosilicate is aged for up to about two and a half hours before diluting the aqueous polysilicate to 0.5 weight % of silica.

The siliceous material may be a colloidal borosilicate. The colloidal borosilicate may be prepared by contacting a dilute aqueous solution of an alkali metal silicate with a cation exchange resin to produce a silicic acid and then forming a heel by mixing together a dilute aqueous solution of an alkali metal borate with an alkali metal hydroxide to form an aqueous solution containing 0.01 to 30 % B_2O_3 , having a pH of from 7 to 10.5.

The swellable clays may for instance be typically a bentonite type clay. The preferred clays are swellable in water and include clays which are naturally water swellable or clays which can be modified, for instance by ion exchange to render

them water swellable. Suitable water swellable clays include but are not limited to bentonite or related swelling clays often referred to as hectorite, smectites, montmorillonites, nontronites, saponite, sauconite, hornites, attapulgites and sepiolites.

Most preferably the clay is a bentonite type clay. The bentonite may be provided as an alkali metal bentonite. Bentonites occur naturally either as alkaline bentonites, such as sodium bentonite or as the alkaline earth metal salt, usually the calcium or magnesium salt. Generally the alkaline earth metal bentonites are activated by treatment with sodium carbonate or sodium bicarbonate. Activated swellable bentonite clay is often supplied as dry powder. Alternatively the bentonite may be provided as a high solids flowable slurry, for example at least 15 or 20% solids.

When the charged microparticulate material comprises an organic cross-linked polymeric microparticles. The microparticles may be made as microemulsions by a process employing an aqueous solution comprising a cationic or anionic monomer and crosslinking agent; an oil comprising a saturated hydrocarbon; and an effective amount of a surfactant sufficient to produce particles of less than about 0.75 micron in unswollen number average particle size diameter.

Microbeads are also made as microgels by procedures described by Ying Huang et. al., Makromol. Chem. 186, 273-281 (1985) or may be obtained commercially as microlatices. The term "microparticle", as used herein, is meant to include all of these configurations, i.e. beads per se, microgels and microlatices.

The charged microparticle material may be used in amounts of at least 0.002% based on weight of suspended solids. Typically though the doses are usually as high as 0.8 or 1.0% or higher. When the charged microparticle material is inorganic, the dose is usually in excess of 0.06%, preferably in the range 0.1 to 0.6%. When the charged microparticle is organic, the dose is typically below 0.3%, preferably in the range 0.02 to 0.1%.

In another preferred embodiment, the solid matter can be separated particularly

rapidly from the liquid phase, when the flocculation is effected by employing a water-soluble or water-swellaable polymer and a charged microparticulate material.

In one aspect, it is particularly preferred when flocculation is effected by introducing an anionic microparticle material into the aqueous mixture and then reflocculating by adding a cationic or substantially non-ionic polymer.

In a further preferred embodiment of the present invention flocculation is effected by introducing a cationic polymer into the aqueous mixture and then reflocculating by adding an anionic microparticulate material.

In a further preferred embodiment of the present invention flocculation is effected by introducing an anionic polymer into the aqueous mixture and then reflocculating by adding a cationic polymer.

In a further preferred embodiment of the present invention flocculation is effected by introducing a cationic polymer into the aqueous mixture and then reflocculating by adding an anionic polymer.

In a preferred embodiment of this invention, the aqueous mixture is obtained from hydrolysis of a polysaccharide based plant derived material.

Another embodiment of the present invention relates to a process of producing fermentation product, which comprises the steps of,

- (i) hydrolysing a particulate polysaccharide based plant derived material in an acid medium, and thereby forming an aqueous mixture comprising dissolved sugar and solid matter,
- (ii) subjecting the aqueous mixture to one or more separation stages in which solid matter is removed from the aqueous phase,
- (iii) adjusting the pH of the obtained aqueous phase to a pH of at least 4,
- (iv) fermenting the dissolved sugars of the aqueous phase by an enzyme to produce a fermentation product,

(v) Isolating the fermentation product,

wherein in at least one separation stage in step (ii) a flocculating agent is added to the aqueous mixture in an effective amount.

Preferably the flocculating agent is selected from the group consisting of water-soluble polymers, water swellable polymers and charged microparticulate material.

The particulate polysaccharide based plant derived material usually is any readily available source of polysaccharides, particularly cellulosic materials. Typically the cellulosic material comprises materials selected from the group consisting of herbaceous biomass, softwood biomass, hardwood biomass, sewage sludge, paper mill sludge and the biomass fraction of municipal solid waste. The herbaceous biomass may for instance be bagasse, rice straw, rice hulls and cotton gin trash.

By concentrated we mean that the acid generally has a concentration of at least 10% by weight. Usually though the concentration will be much higher depending on the chosen acid, for instance at least 15 or 20%, but may be considerably higher, for instance between 25 to 90% or even higher, for instance around 70 to 77% if sulphuric acid is chosen, or around 36 to 37% if hydrochloric acid is chosen. The acid may be a strong mineral acid such as hydrochloric acid, sulphuric acid, sulphurous acid, nitric acid or phosphoric acid. Suitable organic acids may be carbonic acid, tartaric acid, citric acid, glucuronic acid, formic acid, trichloroacetic acid or similar mono- or polycarboxylic acids. The concentrated acid is ideally a strong acid. Ideally the acid exhibits a pKa below 4. Best results are obtained by using either hydrochloric acid or sulphuric acid.

The action of the concentrated acid on the plant derived material results in hydrolysis of the polysaccharides, e.g. cellulose, which forms C₅ and C₆ sugars and various solid by-product materials, mainly lignin. When the sugar liquor is used to produce a fermentation product, it is important that the aqueous sugars

are effectively separated from the lignin and other by-products that would be potentially harmful to the fermentation process. The action of the acid may also result in so-called decrystallisation and release of heavy metals.

Desirably the action of the strong acid is carried out at an elevated temperature. Ideally the temperature can be slightly above room temperature, for example 30°C. Usually though effective digestion of the plant derived material is carried out at higher temperatures, preferably between 50 to 100°C. The material will normally be subjected to acid treatment for at least 30 minutes. Usually the treatment will be much longer, for instance up to 600 or 700 minutes. The period of time required for adequate digestion may vary according to the particular plant derived material used, the strength of the acid and the temperature used. Normally the treatment will be between 40 and 480 minutes. Typically the hydrolysis would be performed at atmospheric pressure.

The hydrolysate is then separated from the solid materials, preferably through pressing of the treated material to separate the residue as a solid product. The solid product that is separated may be subjected to at least one wash cycle and then repeating stages (ii) and (iii), which wash cycle comprises washing the solid product with a suitable wash liquid. The wash liquid may be water. Normally the wash water is recycled water, for instance water that has been separated from the still bottoms liquor in the distillation recovery of the fermentation product in which suspended solids have been removed.

The liquid hydrolysate, which contains sugars and acid, can then be collected for further processing.

It is preferred to adjust the pH of the acid sugar liquor to a pH of at least pH 4.

The pH adjustment may be done by addition of a base or by use of an ion exchange resin, which is capable of absorbing the acid.

In a preferred embodiment of this invention, the added acid as well as undesirable

toxic heavy metals – if present – may be removed by lowering the pH of the acidified aqueous sugar liquor that results from the digestion process to a value of at least 10 by addition of a usual base material such as sodium carbonate, then separating the liquid from the solid phase, e.g. by usual means such as filtration, and afterwards subsequent adjusting of the pH to more neutral or slightly acidic pH. Desirably the pH may be adjusted to a pH of between 10 and 12, preferably about 11, by addition of a base, followed by titrating back to a pH of between 4 and 5, preferably about 4.5.

The acid may be removed from the liquor by adding the hydrolysate to a resin bed and the sugars are absorbed onto the resin and the sugars are absorbed onto the resin. The resin can then be purged with a gas substantially free of oxygen, which pushes the acid out of the resin. The resin can then be washed with water substantially free of oxygen. It would then be possible to produce an aqueous sugar stream. Ideally the sugar stream ideally contains at least 98% of the sugar present in the hydrolysate.

After the separation of the acid from the sugar stream, the acid is preferably concentrated for reuse. The concentration desirably can be achieved by evaporation.

Nutrients may be added in sufficient amounts to permit microbial growth. Typically the nutrients are selected from the group consisting of magnesium, nitrogen, potassium phosphate, trace elements and vitamins are added to the liquor following step (iv) in sufficient amounts to permit microbial growth. The sugar solution is then mixed with a microbial organism known to produce useful fermentation products.

The fermentation process of the present invention typically involves allowing the fermentation to proceed for 3 to 5 days. Volatile fermentation products may be continually removed by recirculating carbon dioxide through a cooled condensing column. Desirably the fermentation products are collected from the condensing

column after three to five days and then distilled. Preferably volatile fermentation products are separated from the broth by passing the broth comprising the fermentation product into a distillation stage, where the fermentation compound is collected as a distillate and the residue 'still bottoms' is removed. Microorganisms can be separated from the fermentation broth or preferably from the still bottoms, preferably through centrifugation and can be recycled for reuse. In one preferred aspect of the invention the fermentation product is separated from the broth by passing the broth comprising the fermentation product into a concentration stage, in which the fermentation compound is collected in the concentrate and extracted by at least one means selected from the group consisting of ion exchange, solvent extraction and electrodialysis.

The process can be used to prepare a range of fermentation products, but preferably the fermentation product is selected from the group consisting of ethanol, glycerol, acetone, n-butanol, butanediol, isopropanol, butyric acid, methane, citric acid, fumaric acid, lactic acid, propionic acid, succinic acid, itaconic acid, acetic acid, acetaldehyde, 3-hydroxy propionic acid, glyconic acid and tartaric acid and amino acids such as L-glutaric acid, L-lysine, L-aspartic acid, L-tryptophan, L-arylglycines or salts of any of these acids.

The microorganisms used in the fermentation process of the present invention can be, for example, a yeast such as *Kluyveromyces* species, *Candida* species, *Pichia* species, *Brettanomyces* species, *Saccharomyces* species such as *Saccharomyces cerevisiae* and *Saccharomyces uvarum*, *Hansenula* species and *Pachysolen* species. Alternatively, the microorganism can be a bacteria such as *Leuconostoc* species, *Enterobacter* species, *Klebsiella* species, *Erwinia* species, *Serratia* species, *Lactobacillus* species, *Lactococcus* species, *Pediococcus* species, *Clostridium* species, *Acetobacter* species, *Gluconobacter* species, *Lactobacillus* species, *Aspergillus* species, *Propionibacterium* species, *Rhizopus* species and *Zymomonas mobilis*. In addition genetically modified strains may also be used.

Since the solid product generally comprises lignin and analogous materials it can be particularly difficult to separate from the liquor. Surprisingly we have found that the production of fermentation product can be significantly improved by applying a particular flocculating agent to the separation of the hydrolysate from the solid product. We have found that the solid product can be more efficiently separated by the process and that a higher cake solids can be achieved. Since the solid product can be more efficiently dewatered there is a reduced requirement for separation equipment capacity, and equipment that is less expensive and less expensive to operate, such as a filter press, can be used. Since higher cake solids can be achieved, less of the acid sugar solution remains in the residual by-product solid. Hence the quantity of water required to wash the by-product solid free of acid and sugar is much reduced.

The employing one or more flocculants in the separation stage – according to the instant invention – results in a more efficient separation of the sugar liquor and the solid product, which in turn enables more fermentation product to be produced. In addition, more lignin can be obtained as solid mass from the inventive process compared to known processes, which can be burnt or used for the manufacture of chemicals. In general, the action of the flocculating agent greatly enhances the separation of the solids from the liquor by comparison to separation using solely mechanical means. We have found that the process of the present invention provides a higher cake solids, with less residual aqueous liquor, which means that a higher proportion of the sugar liquor is available for conversion into the fermentation product. Likewise we find that the aqueous liquor contains much lower levels of extraneous suspended cellulosic solids. Furthermore we also find that less wash water is required.

Example: 100 parts softwood chips are added to 170 parts of 77% sulphuric acid and the temperature is maintained below 80°C, the resulting gelatinous mixture is thoroughly mixed. Then the gelatinous mixture is diluted with water to an acid concentration of 25%. Thereafter, the reaction mixture is heated to a temperature of 100°C for 60 minutes. After hydrolysis, the obtained slurry is fed to a separation

equipment for pressing. Prior to pressing, a flocculant (Ciba®ZETAG®7848, at 0.2% solids, from Ciba Specialty Chemicals) and a particulate suspension (sodium bentonite, at 5% solids) are added into the feed stream with necessary agitation at a dose of 0.2 kg per ton of solids of polymer and 0.5 kg per ton solids of bentonite. The acid sugar solution is separated by pressing from the remaining solids, releasing 35% acid and 17% sugar.

After pressing, the resultant cake containing the solid matter is washed with approximately an equal amount of water. Prior to re-pressing a flocculant solution as above and sodium bentonite as above are added into the feed stream with necessary agitation at a dose of 0.2 kg per ton of solids of polymer and 0.5 kg per ton solids of bentonite. Pressing released 16% acid and 9% sugar.

The recovered biomass cake is then subjected to a repeat process of acid treatment (hydrolysis) above to release further sugar. The resulting cake contains more lignin compared to the content of the first cycle.

Claims

1. A process for improving the separation of solid matter from the liquid phase of an aqueous mixture comprising dissolved sugar, characterized in adding a flocculating agent to the aqueous mixture in an effective amount.
2. The process according to claim 1, wherein the aqueous mixture is obtained from hydrolysis of a polysaccharide based plant derived material.
3. The process according to claims 1 or 2, wherein the amount of flocculating agent is in the range of from 0.002 to 1 % by weight, based on the weight of solid matter.
4. A process of producing fermentation product comprising the steps of,
 - (i) hydrolysing a particulate polysaccharide based plant derived material in an acid medium, and thereby forming an aqueous mixture comprising dissolved sugar and solid matter,
 - (ii) subjecting the aqueous mixture to one or more separation stages in which solid matter are removed from the aqueous phase,
 - (iii) adjusting the pH of the obtained aqueous phase to a pH of at least 4,
 - (iv) fermenting the dissolved sugars of the aqueous phase by an enzyme to produce a fermentation product,
 - (v) isolating the fermentation product,characterised in that in at least one separation stage in step (ii) a flocculating agent is added to the aqueous mixture in an effective amount.
5. A process according to claim 4 in which the plant derived material comprises components selected from the group consisting of herbaceous biomass, softwood biomass, hardwood biomass, sewage sludge, paper mill sludge and the biomass fraction of municipal solid waste.
6. A process according to any of claims 4 to 5 in which the solid matter are

subjected to at least one wash cycle, which wash cycle comprises washing the solid matter and then repeating stages (i) and (ii).

7. A process according to claims 1 to 6 in which the flocculating agent is selected from the group consisting of water-soluble or water swellable natural, semi-natural and synthetic polymers.

8. A process according to claim 7 in which the polymer is selected from the group consisting of polyacrylate salts, polyacrylamide, copolymers of acrylamide with (meth) acrylic acid or salts thereof, copolymers derived from acrylamide and dialkylaminoalkyl (meth)acrylate acid salt or quaternary ammonium salts, polymers derived from diallyldimethyl ammonium chloride, polyamines and polyethylene imines.

9. A process according to any of claims 1 to 6 in which the flocculating agent is a charged microparticulate material.

10. A process according to claim 9 in which the charged microparticulate material is selected from the group consisting of swellable clays, anionic, cationic or amphoteric microparticulate silica based materials and organic cross-linked polymeric microparticles.

11. A process according to any of claims 1 to 6 in which the flocculating agent is a water soluble or water-swellable polymer and a charged microparticulate material.

Abstract

Process for improving the separation of solid matter from the liquid phase of an aqueous mixture comprising dissolved sugar, wherein a flocculating agent is added to the aqueous mixture in an effective amount, and a process of producing fermentation product comprising the steps of,

- (i) hydrolysing a particulate polysaccharide based plant derived material in an acid medium, and thereby forming an aqueous mixture comprising dissolved sugar and solid matter,
- (ii) subjecting the aqueous mixture to one or more separation stages in which solid matter are removed from the aqueous phase,
- (iii) adjusting the pH of the obtained aqueous phase to a pH of at least 4,
- (iv) fermenting the dissolved sugars of the aqueous phase by an enzyme to produce a fermentation product,
- (v) isolating the fermentation product,

wherein in at least one separation stage in step (ii) a flocculating agent is added to the aqueous mixture in an effective amount.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.